



LYRIC THERMOSTAT PLUG-IN FOR HOMESEER HS3

VERSION 3.5

RELEASE DATE: 7/28/2023

CONTENTS

Terms & Conditions	2
Overview.....	3
Installation.....	3
System Requirements.....	3
Configuration	4
Thermostat Configuration	6
Thermostat Devices	7
Command Processing	8
Known Issues	8
Support.....	8
Appendix 1: Files.....	9
Appendix 2: Creating a Resideo Developer Account	10

TERMS & CONDITIONS

Resideo has provided an API for developers and is in control of what capabilities are provided. This means that if Resideo changes their API, work will have to be done on this plug-in to make it compatible, and the type of changes and timing of those changes is outside of my control. Maintenance windows for Resideo’s servers occurs on their schedule as well, which can interrupt the plug-in’s ability to communicate with the servers and control your devices. Your purchase and use of this plug-in is as-is and at your own risk.

Excessive activity on your account may result in your account being suspended, requiring you to call Resideo and get it re-activated. While this plug-in has been designed to minimize the chances of this occurring by implementing preventative measures such as timers and minimum command, update and polling frequencies, these values can be changed by the user. Regardless of the values entered (be they the default, smaller or larger), by activating this plug-in in your Homeseer software, you acknowledge this risk and agree to indemnify and hold harmless the developer of this plug-in, Homeseer Technologies, and any other third party plug-in developers from any damages (including but not limited to financial, time spent, opportunity cost, loss of account privileges, and the inability to remotely control your thermostats or other connected devices).

Lyric™ is a trademark of Resideo Technologies Inc.



OVERVIEW

The skWare Lyric Thermostat Plug-In for Homeseer provides you with a way to monitor and control your Lyric™ Thermostat devices from within Homeseer.

<input type="checkbox"/>		No Status	Thermostat	First Floor	First Floor	2/15/2021 1:19:39 PM	
<input type="checkbox"/>		Success	Thermostat	First Floor	Status	2/16/2021 5:38:41 PM	<input type="button" value="Update"/>
<input type="checkbox"/>		74°F	Thermostat	First Floor	Cool Setpoint	2/16/2021 2:03:17 PM	74°F <input type="button" value="-1"/> <input type="button" value="+1"/>
<input type="checkbox"/>		72°F	Thermostat	First Floor	Heat Setpoint	2/16/2021 9:02:14 AM	72°F <input type="button" value="-1"/> <input type="button" value="+1"/>
<input type="checkbox"/>		Heat	Thermostat	First Floor	System Mode	2/15/2021 1:20:10 PM	<input type="button" value="Cool"/> <input type="button" value="Heat"/> <input type="button" value="Off"/>
<input type="checkbox"/>		Idle	Thermostat	First Floor	Operating Status	2/16/2021 2:28:20 PM	
<input type="checkbox"/>		Heat	Thermostat	First Floor	Operating Mode	2/15/2021 1:20:10 PM	
<input type="checkbox"/>		Auto	Thermostat	First Floor	Fan Mode	2/15/2021 1:20:10 PM	<input type="button" value="On"/> <input type="button" value="Auto"/> <input type="button" value="Circulate"/>
<input type="checkbox"/>		Off	Thermostat	First Floor	Fan Status	2/15/2021 1:20:10 PM	
<input type="checkbox"/>		72°F	Thermostat	First Floor	Indoor Temp	2/16/2021 9:12:15 AM	
<input type="checkbox"/>		56.8°F	Thermostat	First Floor	Outdoor Temp	2/16/2021 5:38:41 PM	
<input type="checkbox"/>		55%	Thermostat	First Floor	Outdoor Humidity	2/16/2021 5:38:41 PM	
<input type="checkbox"/>		None	Thermostat	First Floor	Hold Type	2/15/2021 1:20:10 PM	<input type="button" value="None"/> <input type="button" value="Temporary"/> <input type="button" value="Permanent"/>

INSTALLATION

This Plug-In is installed using the built-in updater capability of Homeseer. New installations include the binaries and supporting files needed to run the Plug-In, and updates will replace any of those items that have changed.

Before you set it up, you must have a working account and a functioning Lyric device. If you are running this plug-in from a Linux platform (including the Zee), you may need to update certain dependencies manually, per the instructions posted on the plug-in's support forum.

SYSTEM REQUIREMENTS

The skWare Lyric Thermostat Plug-In for Homeseer runs on both Windows and Linux installations of HS3 and has been tested with version 3.0.0.148+. Earlier versions of HS3 should work but have not been specifically checked.

On Linux, this plug-in requires at least Mono version 3.8, though Mono 4.8 or higher is recommended for the most current security protocols.

The following devices have been tested with this plug-in, but any Lyric device supported by the Honeywell Connected Home API should work. Please report back via the Homeseer forums if you have success or problems with any specific model.


- [RCHT8610WF](#) - Lyric™ T5 Wi-Fi Thermostat

CONFIGURATION

After installing the plug-in, a new “Lyric Thermostat” menu item can be found under “Plug-Ins” menu in the Homeseer browser interface. The “Configuration” item will take you to the configuration page, where you are able to define your devices and setup additional options for the plug-in.

The first step is to accept the plug-in Terms & Conditions (see above) and connect to your account. The plug-in has a built-in API Key and Secret, but some users have reported “429 Too Many Requests” errors from Resideo, which may be linked to the number of plug-in users on that key without Resideo increasing the limits. Unfortunately, they are unresponsive to requests to increase it. To avoid those errors, optional fields to use your own API account have been provided (see [Appendix 2](#) for instructions on how to set this up). For those who have already connected their accounts, a reconnect will be required if this approach is used, but no devices or events will be affected.

Connecting your account is a three-part process, starting with the plug-in directing you to Honeywell’s service to login, then you must provide authorization to connect your devices to Homeseer. Once you have done so, a code will be provided. The last step is to provide that code to the plug-in so it can connect your device.



Once your account is connected, you will have the option to reset your connection from the account tab. Performing this action will disconnect the plug-in from your Lyric account until you complete the steps again, but it will not remove any related HS devices. Reauthorizing your account may be necessary from time to time.

The “Config” page also provides the control over plug-in behavior and logging output.

The screenshot shows the "Lyric Thermostat Plugin Configuration" page. At the top, there are buttons for "Thermostat List" and "Help". Below that is a checkbox labeled "I accept the Terms & Conditions as outlined in the user documentation provided with this plugin." which is checked. The main configuration area is divided into several sections:

- API Account:** A text box explaining that the plugin uses a shared API key. It includes input fields for "API Key (Optional)" and "API Secret (Optional)".
- Lyric Thermostat Account:** A section with two steps: "Step 1 of 3: Allow the Lyric Thermostat Plugin to access your account and thermostats." and "Step 2 of 3: Enter the code you received:" followed by an input field. A "Reset your connection to the Lyric services" button is also present.
- Communication Settings:** Includes input fields for "Poll Interval" (set to 300, with a note "(min: 300)") and "Update Frequency" (set to 30, with a note "(min: 15)").
- Thermostat Device Settings:** Features a checked checkbox for "Simulate Auto mode for thermostats without native support (Changing this value may invalidate existing events.)".
- Logging Options:** Includes a checkbox for "Enable Debug Logging (recommended only for support)" which is unchecked. At the bottom of this section are "Clear Log File" and "Download Log File" buttons.

The polling interval (in seconds) specifies how often HS should login to the website and check the current settings. A value of 300 seconds (5 minutes) or higher is required.


The “Update Frequency” controls how much time must pass between update requests. These are specific requests outside of the polling window requested manually (via the “Update” button or script commands). A value of 15 seconds or higher is required. Requests made within less time than this will result in a “Waiting for update...” status temporarily, until the 15 seconds have passed.

For thermostats that do not support “Auto” mode, the Plug-in can simulate this capability if you enable it. If the Indoor Temperature is greater than the Cool Setpoint or lower than the Heat Setpoint, the operating mode will be changed automatically. You must maintain a 3 degree difference between Cool and Heat Setpoints.

Optional log data can be recorded in both the Homeseer log and in a stand-alone Plug-In log (which can be found in the “Logs” directory of your Homeseer installation). Please note that Debug Logs should only be used when troubleshooting or sending in for support as it can have a significant impact on performance.

The “Download Log File” and “Clear Log File” buttons on this page make it easier to manage the plug-in log files on your server, as you are no longer required to access the file system to get them when requested for support.

THERMOSTAT CONFIGURATION



Once your account is connected, the “Thermostat List” Page will be added to the plug-in menu, where you can add one or more thermostats to be controlled by Homeseer by selecting the location and device you wish to add.

You can edit the minimum and maximum allowed cool or heat

settings for each device – these do not replace the settings on the thermostat, but rather are specific to Homeseer. Attempting to go above or below these values is not allowed in Homeseer events, and if a change beyond these limits is detected on a status update, it will be adjusted up/down to the limit accordingly.

When you’ve added your device to the list, the initial parent device will be created. After the first polling of the status occurs, a series of child devices will be created based on the capabilities of your Lyric device, including:

- Root Device
- Update Status
- Fan Mode
- System Mode
- Operating Mode
- Operating Status
- Cool Setpoint
- Heat Setpoint
- Hold Type
- Indoor Temperature
- Indoor Humidity
- Outdoor Temperature
- Outdoor Humidity
- Emergency Heat

You can also highlight a thermostat in the list and click “Remove”, which will delete the associated devices.

THERMOSTAT DEVICES

Once your thermostats are configured, your devices will show the current values on the Home screen.

<input type="checkbox"/>	 No Status	Thermostat	First Floor	First Floor	2/15/2021 1:19:39 PM	
<input type="checkbox"/>	 Success	Thermostat	First Floor	Status	2/16/2021 5:38:41 PM	<input type="button" value="Update"/>
<input type="checkbox"/>	 74°F	Thermostat	First Floor	Cool Setpoint	2/16/2021 2:03:17 PM	74°F ▾ -1 +1
<input type="checkbox"/>	 72°F	Thermostat	First Floor	Heat Setpoint	2/16/2021 9:02:14 AM	72°F ▾ -1 +1
<input type="checkbox"/>	 Heat	Thermostat	First Floor	System Mode	2/15/2021 1:20:10 PM	<input type="button" value="Cool"/> <input type="button" value="Heat"/> <input type="button" value="Off"/>
<input type="checkbox"/>	 Idle	Thermostat	First Floor	Operating Status	2/16/2021 2:28:20 PM	
<input type="checkbox"/>	 Heat	Thermostat	First Floor	Operating Mode	2/15/2021 1:20:10 PM	
<input type="checkbox"/>	 Auto	Thermostat	First Floor	Fan Mode	2/15/2021 1:20:10 PM	<input type="button" value="On"/> <input type="button" value="Auto"/> <input type="button" value="Circulate"/>
<input type="checkbox"/>	 Off	Thermostat	First Floor	Fan Status	2/15/2021 1:20:10 PM	
<input type="checkbox"/>	 72°F	Thermostat	First Floor	Indoor Temp	2/16/2021 9:12:15 AM	
<input type="checkbox"/>	 56.8°F	Thermostat	First Floor	Outdoor Temp	2/16/2021 5:38:41 PM	
<input type="checkbox"/>	 55%	Thermostat	First Floor	Outdoor Humidity	2/16/2021 5:38:41 PM	
<input type="checkbox"/>	 None	Thermostat	First Floor	Hold Type	2/15/2021 1:20:10 PM	<input type="button" value="None"/> <input type="button" value="Temporary"/> <input type="button" value="Permanent"/>

The “Status” device shows the status of the last request or command and tracks the last data refresh date/time.

The “Indoor Temp”, “Indoor Humidity”, “Outdoor Temp”, and “Outdoor Humidity” devices are status-only displays of the data last reported at the thermostat’s location, and are included based on your thermostat’s capabilities.

The “Fan Mode” shows what the setting is (“On” or “Auto”) and provides control buttons to change the mode.²

The “Fan Status” device indicates whether the fan is actually running at this time or not (“On”, “Off”).¹

The “Cool Setpoint” and “Heat Setpoint” devices shows what the current setpoint is. It provides a dropdown of valid values to adjust the setpoint for the current mode, as well as +1/-1 adjustments (or +0.5/-0.5 for Celsius). If the device is currently in a Permanent Hold, that hold will be maintained, otherwise a temporary hold will be issued if your thermostat supports such a capability.²

The “Hold Type” device shows whether the thermostat is following the schedule (“None”), in a Temporary Hold (“Until HH:MM”) or a “Permanent” hold, depending on capabilities. Buttons are provided to change the type of hold in place.²

The “System Mode” shows what the setting is (“Cool”, “Heat”, “Auto” or “Off”, as appropriate to your thermostat model) and provides control buttons to change the mode². If you have enabled the “Simulate Auto” option, an “Auto” mode button will be added even if your thermostat doesn’t support it natively, and switching will be handled by the plug-in if the temperature exceeds the cool setpoint or drops below the heat setpoint.

The “Operating Status” is an indication of whether the system is currently running or not (“Idle”, “Heating”, “Cooling”), and the “Operating Mode” device that shows the mode the unit is currently working in when Auto (or Simulated Auto) is used.

The “Emergency Heat” device is turned on when emergency heat is activated on your thermostat.

COMMAND PROCESSING

In an effort to prevent excessive commands from being sent, when an update is requested, the plug-in checks the timestamp of the last requested update for that thermostat and if it's too soon (based on "Update Frequency"), it sets a timer to wait until the "Update Frequency" has passed, then requests the update. Any polling timers are stopped and restarted each time an update occurs, so if you change the setpoint (which also requests an update), the next polling won't occur for the specified number of seconds ("Polling Interval") regardless of how long ago the last poll occurred.

KNOWN ISSUES

1. The Lyric API doesn't properly report Fan Status, so it currently shows as "Off" at all times. I'm awaiting a response from Honeywell on this issue.
2. Attempts to initiate changes from the plug-in to the thermostat using the Lyric API will fail with a "400 (Bad Request) Device Not Found" error if you have created your own Resideo Developer account and your application was created using spaces or other punctuation.

SUPPORT

Support for the skWare Lyric Thermostat Plug-In for Homeseer is provided through the standard Homeseer channels. The primary mechanism is via the [Lyric Thermostat Plug-in forum](#) on the Homeseer website. The author can be contacted directly at steve@skware.net.

APPENDIX 1: FILES

The following files are used by the Plug-In. Directories in bold are part of the standard Homeseer installation. Files marked with * are created by the software during usage; all other files are included in the installation.

<Homeseer Installation Directory>

```

HSPI_SKWARE_HW_LYRIC.exe
HSPI_SKWARE_HW_LYRIC.exe.config
\Bin
  \skWare
    \LyricThermostat
      Newtonsoft.Json.dll
      skWare.Common.dll
      skWare.Common.HS3.dll
      skWare.Homeseer.LyricThermostat.Core.dll
      skWare.Homeseer.LyricThermostat.Core.dll.config
      Microsoft.IdentityModel.Abstractions.dll
      Microsoft.IdentityModel.Logging.dll
      Microsoft.IdentityModel.Tokens.dll
  \Config
    HSPI_SKWARE_HW_LYRIC.ini*
  \Docs
    \skWare
      \LyricThermostat
        skWare Lyric Thermostat Plug-In User Guide.pdf
  \html
    \LyricThermostat
      \images
        auto.png
        auxheat.png
        cool.png
        emergheat.png
        failed.png
        fan-auto.png
        fan-circulate.png
        fan-off.png
        fan-on.png
        fan-scheduled.png
        heat.png
        humidity.png
        nostatus.png
        off.png
        permanent.png
        schedule.png
        temporary.png
        Thermometer-cool-0.png
        Thermometer-cool-1.png
        Thermometer-cool-2.png
        Thermometer-cool-3.png
        Thermometer-cool-4.png
        Thermometer-cool-5.png
        Thermometer-generic-0.png
        Thermometer-generic-1.png
        Thermometer-generic-2.png
        Thermometer-generic-3.png
        Thermometer-generic-4.png
        Thermometer-generic-5.png
        Thermometer-heat-0.png
        Thermometer-heat-1.png
        Thermometer-heat-2.png
        Thermometer-heat-3.png
        Thermometer-heat-4.png
        Thermometer-heat-5.png
  \Logs
    HSPI_SKWARE_HW_LYRIC.log*

```

APPENDIX 2: CREATING A RESIDEO DEVELOPER ACCOUNT

In order to leverage your own API key and secret to avoid the “429 Too Many Requests” errors, you must establish your own **Developer Account**. This is separate from your **Thermostat Account**, which is used to login and authorize the plug-in.

Step 1: Create an Account

Sign up for an account on the Resideo developer site: <https://developer.honeywellhome.com/user/register>

Step 2: Register an App

User the “Create New App” button to define a new App that will use the Honeywell Connected Home API. The App Name must be unique, so I suggest adding your own name to the end or something similar. **In order to avoid a potential issue with control requests, make sure your app name uses alphanumeric characters only – no spaces or punctuation.**

The screenshot shows a web browser window with the URL `developer.honeywellhome.com/user/me/apps/add`. The page features the Resideo logo and a navigation menu with items: GUIDES, APIS, EVENTS, FAQs, MY ACCOUNT, MY APPS, and LOG OUT. The main form contains the following fields:

- App Name ***: lyricpluginshill
- Internal name:** lyricpluginshill (with an `Edit` link)
- Callback URL ***: https://skware-oauth-hs.azurewebsites.net/api/OAuthCallback

A blue button labeled `Save Changes` is located below the form fields.

The “Callback URL” must be: <https://skware-oauth-hs.azurewebsites.net/api/OAuthCallback>

Step 3: Get the Key & Secret

The screenshot shows the 'Keys' page for the application 'lyricpluginshill'. The page has a 'new' badge and an 'Approved' status. There are tabs for 'Keys' and 'Analytics'. Below the tabs, there is a section titled 'lyricpluginshill's Keys' with the following text:

Below are keys you can use to access the API products associated with this application (*lyricpluginshill*). The actual keys need to be approved *and* approved for an *API product* to be capable of accessing any of the URIs defined in the API product.

Consumer Key	[Redacted]
Consumer Secret	[Redacted]

Step 4: Add Key & Secret to Plug-in

Thermostat List Documentation

I accept the Terms & Conditions as outlined in the user documentation provided with this plugin.

Lyric Thermostat Plugin Configuration

API Account

This plugin uses a shared API key, which may be subject to rate limits by Honeywell. To use the built-in account, leave these fields blank. To create your own account (recommended), please see the documentation and provide the Key and Secret here.

Note: changing either of these values will reset your authorization and you will need to reconnect your plugin below.

API Key (Optional)

API Secret (Optional)

Lyric Thermostat Account

[Reset your connection to the Lyric services](#)

After you change the Key and Secret, you will be disconnected from your Lyric account. Follow the normal steps to authorize your new Resideo App to connect to your thermostat (on Resideo's page you'll now see your App name from step 2). Be sure and use your **Thermostat Account** for this step.

Once you get the code and provide it to the plug-in, your thermostat should successfully update without the 429 errors.